



# iSPOS 195



Specifications	iSPOS 195	
Processor	Intel Celeron Processor J1900 up to 2.42 GHz	
System Memory	1*SO-DIMM, DDR3L 1066/1333, Max. 4GB	
Display	15" LED backlight TFT LCD, 1024*768, 250 cd/m <sup>2</sup>	
Touch Screen	Projected Capacitive Touch	5-wire Resistive Touch
Operation System	Win 7 SP1, POSReady 7 Win 8.1, Windows Embedded 8.1 Industry, Ubuntu 14.04	
<b>External I/O Ports</b>		
USB port	4*USB2.0	
Serial port	2*DB-9	
Cash Drawer	1*RJ-11	
Keyboard	1*PS/2	
LAN port	1*RJ-45 (10/100/1000 Mbps)	
VGA or Parallel	1*DB-15 or 1*DB-25	
Others	2*Built-in Speakers, 1*Mic, 1*Line out	
<b>Mechanical &amp; Environment</b>		
Dimensions & Weight	389(W)*232(D)*369(H) mm, 8.5 Kgs	
Safety Certifications & IP Rating	FCC/CE, IP 66 Compliance	
Storage & Operating Temp.	-20°C ~ 60°C, 0°C ~ 40°C	
Relative Humidity	10% ~ 90% (non-condensing)	
Power Consumption	60 W maximum	
<b>Peripheral Options</b>		
Wireless LAN	Integrated 802.11 b/g/n Wireless LAN	
Customer Display	SENON iSMON 8.4	VFD 20*2 lines Display
Magnetic Card Reader	Single Track, Double Tracks, Triple Tracks	
Identification Devices	RFID (ISO/IEC 14443A/ 13.56 MHz/ Mifare S50)	
	Fingerprint Reader	
	i-Button	